

You are not logged in.

[Healthcare NLP Technology](#)

Automate coding, indexing, clinical data extraction from free text!

www.rezziliant.com



Ads by Google

Pages: 1

[Index](#) » [AppleScript](#) | [OS X](#) » text edit: using bold text

2009-08-13 07:50:56 am

#1

retepp

Member

From: Netherlands

Registered: 2007-03-29

Posts: 162



Below is a part of my script.

Is it possible to tell text edit to use bold text?

For example: only "archivejob" must be bold

❏ **Open this Scriptlet in your Editor:**

```
property archivedir : "/Volumes/Archief/DTP/test"
```

```
property parentdir : "/Volumes/DTP"
```

```
property archivedir_p : "/Volumes/Archief/DTP/test/permanent"
```

```
property archivedir_t : "/Volumes/Archief/DTP/test/tijdelijk"
```

```
property p_dups : "/dups"
```

```
set chosenfile to (choose file)
```

```
set filecont to read chosenfile
```

```
set archivejobs to paragraphs of filecont
```

```
tell application "TextEdit"
```

```
  activate
```

```
  close every document saving no
```

```
  make new document
```

```
  set the name of window 1 to "Archive Info"
```

```
  set currentText to text of front document
```

```
  set newText to currentText & return & "Starting archiving " & (current date) &
```

```
return & return
```

```
  set text of front document to newText
```

```
end tell
```

```
try
```

```
  do shell script "cd " & archivedir_p & p_dups
```

```
on error
```

```
  do shell script "/bin/mkdir -p " & archivedir_p & p_dups
```

```
end try
```

```
repeat with archivejob in archivejobs
```

```
  set {tid, AppleScript's text item delimiters} to {AppleScript's text item delimiters, {" "}}
```

```
  set pgraphParts to text items of archivejob
```

```
  set testResult to false
```

```
  try
```

```
    set testResult to (((item 1 of pgraphParts) + 0) = item 1 of pgraphParts as integer)
```

```
    set testResult to testResult and {"t", "p"} contains (second item of pgraphParts)
```

```
  end try
```

```
  set testResult to testResult and (length of archivejob = 7)
```

```
  if testResult then
```

```
    tell application "TextEdit"
```

```
      set currentText to text of front document
```

```
      set newText to currentText & return & "this " & archivejob & " is correct " & (current date) & return
```

```
      set text of front document to newText
```

```
    end tell
```

```
  end repeat
```

-- Peter --

SpiritBlade

Member

From: Italy

Registered: 2009-08-13

Posts: 2

[Send Text &Email By Voice](#)

Works on ANY mobile
phone Free 30 day trial
www.voiceassist.com



Ads by Google

Hi! Try with this feature to append data to TextEdit instead of paste and copy. 😊

Tested with PPC G4 10.4.11

🔗 [Open this Scriptlet in your Editor:](#)

```
property archivedir : "/Volumes/Archief/DTP/test"
property parentdir : "/Volumes/DTP"
property archivedir_p : "/Volumes/Archief/DTP/test/permanent"
property archivedir_t : "/Volumes/Archief/DTP/test/tijdelijk"
property p_dups : "/dups"

set chosenfile to (choose file)
set filecont to read chosenfile
set archivejobs to paragraphs of filecont

tell application "TextEdit"
    activate
    close every document saving no
    make new document
    set the name of window 1 to "Archive Info"
    set currentText to text of front document
    set newText to currentText & return & "Starting archiving " & (current date) &
return & return
    set text of front document to newText
end tell

try
    do shell script "cd " & archivedir_p & p_dups
on error
    do shell script "/bin/mkdir -p " & archivedir_p & p_dups
end try

repeat with archivejob in archivejobs

    set {tid, AppleScript's text item delimiters} to {AppleScript's text item delimiters,
{" "}}
    set pgraphParts to text items of archivejob
    set testResult to false

    try
        set testResult to (((item 1 of pgraphParts) + 0) = item 1 of pgraphParts as
integer)
        set testResult to testResult and {"t", "p"} contains (second item of
pgraphParts)
    end try

    set testResult to testResult and (length of archivejob = 7)

    if testResult then
        set endText to (" is correct " & (current date) & return & return)

        my appendMe(false, false, true, "this ")
        my appendMe(true, false, true, archivejob)
        my appendMe(false, false, false, endText)

        (*
tell application "TextEdit"
    set currentText to text of front document
```

regulus6633**Member**

From: Lexington Park, MD

Registered: 2006-11-01

Posts: 1097

Offline

Post #2 here shows how...

<http://macscripter.net/viewtopic.php?id=24219>

Hank

<http://www.hamsoftengineering.com>

Pages: 1

[Index](#) » [AppleScript](#) | [OS X](#) » text edit: using bold text

Jump to

Powered by [FluxBB](#)

Go

[Generated in 0.297 seconds, 8 queries executed]

[Large Group Text Messages](#)Text Large Groups at Once for Free!
Text from Web or Cell phone.

TXTblaster.com

[FileMaker & Automator](#)Integrate FileMaker with InDesign,
Quark, and more with Automator!www.AutomatedWorkflows.com**[Newman's Extra Bold](#)**Shoffee.com has Newman's Extra
Bold Coffee for only \$10.99 per box.Shoffee.com/Newmans_OrganicAds by [RSS](#) [NEW TOPICS](#)[RSS](#) [ACTIVE TOPICS](#)