

Nginx Configuration Directives

- 5 Directives

- [5.1 set_if_empty](#)
- 5.2 set_quote_sql_str
- 5.3 set_quote_pgsql_str
- 5.4 set_quote_json_str
- 5.5 set_unescape_uri
- 5.6 set_escape_uri
- 5.7 set_hashed_upstream
- 5.8 set_encode_base32
- 5.9 set_misc_base32_padding
- 5.10 set_decode_base32
- 5.11 set_encode_base64
- 5.12 set_decode_base64
- 5.13 set_encode_hex
- 5.14 set_decode_hex
- 5.15 set_shal
- 5.16 set_md5
- 5.17 set_hmac_shal
- 5.18 set_random
- 5.19 set_secure_random_alphanum
- 5.20 set_secure_random_lcalpha
- 5.21 set_rotate
- 5.22 set_local_today
- 5.23 set_formatted_gmt_time
- 5.24 set_formatted_local_time

```
1 location /hello {
2     set_unescape_uri $name $arg_name;
3     set_if_empty $name "Anonymous";
4     echo "Hello, $name!";
5 }
```

```
$ >> curl http://localhost/hello
Hello, Anonymous
```

```
$ >> curl http://localhost/hello?name=Johnny
Hello, Johnny
```